

EK425 Gator® Battery Powered Crimping Tool



- Slim profile and light weight permit one hand operation.
- Crimping jaws automatically open to signal that crimp is complete.
- Crimping jaws can be opened in mid-cycle to adjust connector.
- When equipped with CJD3 crimping jaws, can be used with all industry "W" style crimping dies. When equipped with CJK crimping jaws, can be used with dies for Kearney Type "O" tools.
- Crimping jaws are PVC coated on outside edges.
- Carrying strap makes tool easy to carry and to hang in buckets.
- Interchangeable crimping jaws rotate 360°.
- Two batteries, battery charger, and molded carrying case included.
- Choice of 120 volt, 12 volt, or 230 volt battery charger.
- Can cut up to 4/0 ACSR cable when equipped with KD6-27 cutter dies.

CAT. NO.	UPC NO.	DESCRIPTION
EK425-D11	11311	Crimping Tool w/CJD3 crimping jaws w/120 volt battery charger
EK425-D12	11312	Crimping Tool w/CJD3 crimping jaws w/12 volt battery charger
EK425-D22	11313	Crimping Tool w/CJD3 crimping jaws w/230 volt battery charger
EK425-K11	11314	Crimping Tool w/CJK crimping jaws w/120 volt battery charger
EK425-K12	11327	Crimping Tool w/CJK crimping jaws w/12 vol battery charger
EK425-K22	11328	Crimping Tool w/CJK crimping jaws w/230 volt battery charger
CJO	03444	Crimping Jaw Unit- O die profile
CJD3	03242	Replacement Crimping Jaw Unit – D3 dies
CJK	04829	Replacement Crimping Jaw Unit – Kearney O dies

SPECIFICATIONS	
Weight	5.4 lb. (2.47 kg)
Length	18" (465 mm)
Width (head open)	4" (8 mm)
Crimping Force	5 tons (44 kN)
Battery	9.6 Volt, 1.3 Ah
Crimp Cycle Time	~ 6 seconds
Battery Charge Time	1 hour

DIES FOR USE WITH CJD3 CRIMPING JAWS

"W"-STYLE DIES

CAT. NO.	UPC NO.	BURNDY NO.	CAT. NO.	UPC NO.	BURNDY NO.
KD6-10	10165	W-BG	KD6-18	10173	W-166
KD6-11	10166	W-O	KD6-19	10174	W-243
KD6-12	10167	W-C	KD6-20	10175	W-247
KD6-13	10168	W-K840	KD6-21	10176	W-249
KD6-14	10169	W-161	KD6-22	10177	W-164
KD6-15	10170	W-162	KD6-24	10179	W-237
KD6-16	10171	W-163	KD6-25	10180	W-239
KD6-17	10172	W-165			

CRIMPING DIE COMPATIBILITY

CJD3 CRIMPING JAWS

Greenlee	KD6 Series
FCI Burndy	W, X Series
IlSCO	ND Series
Huskie	HT-58 Series
Panduit	CD-2001 Series
CJK CRIMPING JAWS	
Kearney	dies for Type "O" tools

ASCR CUTTING DIES FOR USE WITH CJD3 CRIMPING JAWS

4/0 CAPACITY

CAT. NO.	UPC NO.	BURNDY NO.
KD6-27	10182	W-28K

CONNECTOR CAPACITY

- 5/8" Service Entrance Connectors: 10-1/0 AWG
- .840 Service Entrance Connectors: 1/0-4/0 AWG
- Aluminum "H" Taps: 6-4/0 AWG
- Copper "H" Taps: 10-2 AWG
- Copper Tension Splices: 6-2/0 AWG
- All Aluminum Tension Splices: 6-4/0 AWG
- One Piece ACSR Tension Splices: 4-1/0 AWG
- Two Piece ACSR Tension Splices: 2 AWG-477 kcmil
- Aluminum Jumper Splices: 4 AWG-266.8 kcmil
- Stirrups: 2-4/0 AWG
- Copper color-coded lugs and splices: 8 AWG-500 kcmil
- Aluminum color-coded lugs and splices: 8-4/0 AWG