

HPD Series Sign Post Drivers



Power to Drive Posts Fast

Fairmont's new HPD series sign post drivers are designed to drive posts fast and straight. They have plenty of power to drive a variety of post sizes and types from small delineator posts all the way up to 3 ½" round posts—including square, "U" channel, breakaway stubs, round, "T" fence, and wood. With dual guide handles and interchangeable adapters to match different post styles, it's easy to keep posts straight and oriented so the sign faces the right direction.

The HPD drivers can be operated either from hydraulic circuits on trucks or from stand-alone hydraulic power units.

The HPD drivers can be ordered either with an integral feathering trigger or with a remote on/off valve attached to 70" long hoses.

The HPD-T models with feathering trigger are most often used when the operation requires driving short stub posts into which full height posts will be inserted. The HPD-HV models with the remote on/off valve are usually used when full height posts are to be driven.

PRODUCT FEATURES

- **Quick change front head design** accommodates adapters for different types of posts.
- **Dual guide handles** for good directional control.
- **A deep rod opening** and smooth operation ensures that the driver will not jump off of rods.
- **Can be used with** open- and closed-center hydraulic systems.
- **Available with** integral feathering trigger or remote on/off valve.

SPECIFICATIONS

Hydraulic System Open- and closed-center.

Weight w/UA adapter and hoses 75 lbs. (34.0 kg).

Length 32" (813 mm).

Flow Range 5-8 gpm (18-30 lpm).

Blows/minute @ 8 gpm (30 lpm) 1500.

Maximum Input Pressure 2000 psi (138 bar).

HPD-T Hose length on HPD-HV models 70" (178 cm).

HPD-T on/off hose connection sizes

Pressure hose ½" NPTF

Return hose ½" NPTF

HPD-HV Valve Connection Ports

On/off valve pressure port 9/16-18 SAE O-Ring boss

On/off valve return port 9/16-18 SAE O-Ring boss

ORDERING INFORMATION

CAT. NO.	UPC NO.	DESCRIPTION	QUANTITY
HPD-T-U	11183	Sign post driver w/integral trigger w/universal post adapter	1
HPD-T-R	11184	Sign post driver w/integral trigger w/3.8" (96mm) round post adapter	1
HPD-T-S	11185	Sign post driver w/integral trigger w/2 1/8" square post adapter	1
HPD-HV-U	11186	Sign post driver w/remote on/off valve w/universal post adapter	1
HPD-HV-R	11187	Sign post driver w/remote on/off valve w/3.8" (96 mm) post adapter	1
HPD-HV-S	11188	Sign post driver w/remote on/off valve w/2 1.8" square post adapter	1
RA96	49532	3.8" (96 mm) round post adapter	1
UA	49533	Universal post adapter	1
SA54	49534	2 1/8" square post adapter	1
SPA175SQ	03237	Drive cap for 1 3/4" square posts	1
SPA2SQ	03236	Drive cap for 2" square posts	1

RECOMMENDED FITTINGS

CAT. NO.	UPC NO.	DESCRIPTION
HPD-T		
F020196K	41778	HTMA Female Coupler
F020197K	41779	HTMA Male Coupler
HPD-HV		
54923	54923	HTMA Male Coupler
54924	54924	HTMA Female Coupler

DISTRIBUTED BY

USA	800-435-0786	Fax: 800-451-2632
	815-397-7070	Fax: 815-397-1865
Canada	800-435-0786	Fax: 800-524-2853
International	+1-815-397-7070	Fax: +1-815-397-9247

4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070
 ©2003 Greenlee Textron • An ISO 9001 Company • Printed in USA
 Greenlee Textron is a subsidiary of Textron Inc.

www.fairmont.textron.com

MA-4430 9/03

